



Model TM SERIES 渦輪式流量計

Electronic Digital Turbine Meter

f ”

• ””

TM SERIES – SPECIFICATIONS

Design Type:	Turbine	
Fitting Size:	1/2" 3/4" 1" 1-1/2" 2"	
Fitting Type:	Schedule 80 Spigot (Pipe) End or NPT (Female)	
Flow Range:		
1/2" - TM050:	1 - 10 GPM (3.8 - 38 LPM)	
3/4" - TM075:	2 - 20 GPM (7.6 - 76 LPM)	
1" - TM100:	5 - 50 GPM (19 - 190 LPM)	
1-1/2" - TM150:	10 - 100 GPM (38 - 380 LPM)	
2" - TM200:	20 - 200 GPM (76 - 760 LPM)	
Accuracy:	± 3.0% of reading	
Pressure Rating:	225 PSIG / 15.3 BAR at 73° F (23° C)	
Operating Temperature:	+32° F to +140° F (0° to +60° C)	
Battery Life:	5 Years	
Wetted Materials:		
Housing:	PVC	
Bearings:	Ceramic	
Shaft:	Tungsten Carbide	
Rotor:	PVDF	
Rings:	316 Stainless Steel	
Shipping Weight (approx.):	Spigot	NPT
1/2" - TM050:	.38 lbs. (.172 kg)	.55 lbs. (.249 kg)
3/4" - TM075:	.43 lbs. (.304 kg)	.67 lbs. (.304 kg)
1" - TM100:	.49 lbs. (.222 kg)	.49 lbs. (.381 kg)
1-1/2" - TM150:	.66 lbs. (.299 kg)	1.38 lbs. (.626 kg)
2" - TM200:	.78 lbs. (.354 kg)	1.78 lbs. (.807 kg)
Display Features:	Rate of Flow, Batch and Cumulative Totals, Field Calibration available	
Pulse Output:	Open Collector (NPN)	

APPROVALS



ACCURACY: ±3.0% READING

Features and Benefits:

- ✓ Easy to install.
- ✓ Displays in gallons, litres and cubic feet.
- ✓ Indicates Batch, Cumulative Totals and Rate of Flow.
- ✓ Available in NPT or Spigot fittings.
- ✓ Meets Schedule 80 specifications.
- ✓ Lithium battery life: 5 years.
- ✓ Non-volatile totals means amounts are retained when batteries are replaced or power is lost.



Applications:

- OEM water treatment equipment / skids
- Small waste water treatment equipment
- Sub-metering of facility water usage
- Water based cooling systems

新政儀器有限公司

TEL:(02)26940177 (02)26949824 FAX:(02)26946663

www.hsinjeng.com.tw E-mail : hsin.jeng@msa.hinet.net