



Model TM SERIES 3" & 4" 渦輪式流量計

Flange Model

Spigot Model

NPT Model

®



TM SERIES – SPECIFICATIONS			
Design Type:	Turbine		
Fitting Size:	3" 4"		
Fitting Type:	Schedule 80 Spigot (Pipe) End, NPT (Female) or 150# ANSI Flange		
Flow Range:			
3" - TM 300:	40 - 400 GPM (151 - 1514 LPM)		
Extended Range:	30 - 600 GPM (131 - 2271 LPM)		
4" - TM400:	60 - 600 GPM (227 - 2271 LPM)		
Extended Range:	40 - 800 GPM (151 - 3028 LPM)		
Accuracy:	± 3.0% of reading		
Pressure Rating:	225 PSIG / 15.3 BAR at 73° F (23° C)		
For CE Applications:	135 PSIG / 9.1 BAR at 73° F (23° C)		
Operating Temperature:	+32° F to +140° F (0° to +60° C)		
Battery Life:	5 Years		
Wetted Materials:			
Housing:	PVC		
Bearings:	PEEK		
Shaft & Thrust Washers:	Stainless Steel		
Rotor & Nose Cone:	Acetal		
Signal Generator:	Ferrite		
Shipping Weight (approx.):	Spigot	NPT	Flange
3" - TM300:	2.4 lbs. (1.09 kg)	3.9 lbs. (1.77 kg)	5.8 lbs. (2.63 kg)
4" - TM400:	3.7 lbs. (1.68 kg)	6.1 lbs. (2.77 kg)	9.2 lbs. (4.17 kg)
Display Features:	Rate of Flow, Batch and Cumulative Totals, Field Calibration available		
Pulse Output:	Open Collector (NPN)		

ACCURACY: ±3.0% READING

Features and Benefits:

- ✓ Available in Spigot, NPT and Flange fittings.
- ✓ Displays in gallons, litres and cubic feet.
- ✓ Indicates Batch, Cumulative Totals and Rate of Flow.
- ✓ One-piece field replaceable turbine assembly.
- ✓ Spigot models may be cut to length.
- ✓ Meets Schedule 80 specifications.
- ✓ Lithium battery life: 5 years.
- ✓ Non-volatile totals means amounts are retained when batteries are replaced or power is lost.



Applications:

- OEM water treatment equipment / skids
- Sub-metering of facility water usage
- Waste water treatment equipment
- Chemical feed systems
- Cooling towers
- Irrigation

新政儀器有限公司

TEL:(02)26940177 (02)26949824 FAX:(02)26946663
www.hsinjeng.com.tw E-mail : hsin.jeng@msa.hinet.net