

# 新政 Model WP 螺旋型水錶

## HSIN JENG PROPELLER TYPE WATER METER

### MODEL WP

WP-FC

WP-S1/S2

WPS-FCD

7 位數



6 位數



Register 計數器：Plastic roller counter or metal roller counter with enamelled coating  
塑膠數字輪或金屬琺瑯數字輪，可選擇 7 位數數字輪顯示或 6 位數數字輪顯示 (單位 M3)

### DIMENSIONS WP.WPS

m/m

### WP.WPS規格表 SPECIFICATION

型號 Model	序號 Code	說明 Description
WP,WPS		6位數或7位數數字輪顯示積算值 ( 6 or 7 digits totalizer )
口徑 Size (mm)	50	50mm( 2 ")
	65	65mm( 2 1/2 ")
	75	75mm( 3 ")
	100	100mm( 4 ")
	125	125mm( 5 ")
	150	150mm( 6 ")
	200	200mm( 8 ")
	250	250mm( 10 ")
	300	300mm( 12 ")
	350	350mm( 14 ")
	400	400mm( 16 ")
	450	450mm( 18 ")
材質 Material	-FC	外殼:鑄鐵 Body:Casting Iron 接液部:銅合金 Wetted parts:Brass 葉輪:PP Resin Vane Wheel:PP Resin
	-FCD	外殼:球狀石墨鑄鐵 Body:Ductile Iron 接液部:銅合金 Wetted parts:Brass 葉輪:PP Resin Vane Wheel:PP Resin
	-S1	外殼:SS304 Body:SS304 接液部:SS304 Wetted parts:SS304 葉輪:PP Resin Vane Wheel:PP Resin
	-S2	外殼:SS316 Body:SS316 接液部:SS316 Wetted parts:SS316 葉輪:PP Resin Vane Wheel:PP Resin
	-F0	JIS 10K FLANGE
	-F1	ANSI 150LB FLANGE
接續方式 Connection	-F2	JIS 7.5K FLANGE
	-N	室溫 Normal Temp( 50°C )
	-H	高溫 High Temp( 100°C )

Size of Meter 口徑 (m/m)	Flow Range M <sup>3</sup> /Hr			Length 表長 mm	
	小流量 Min.	連續流量 Cont	最大瞬間 Max.	WP	WPS
50mm( 2 ")	5	16	24	335	207
65mm( 2 1/2 ")	6	30	50	335	207
75mm( 3 ")	6	40	66	335	207
100mm( 4 ")	8	80	126	335	207
125mm( 5 ")	17	150	204	335	207
150mm( 6 ")	20	188	288	430 560	300
200mm( 8 ")	23	240	360	485 560	350
250mm( 10 ")	28	320	500	560	450
300mm( 12 ")	35	450	720	660	500
350mm( 14 ")	58	667	1200	660	500
400mm( 16 ")	81	878	1386	660	600
450mm( 18 ")	104	1040	1663	660	600
500mm( 20 ")	125	1267	2080	660	600
600mm( 24 ")	185	1832	2772	660	800

### Remarks :

- 適用流體：清水、放流水 ( 需加裝過濾器 )。
- 法蘭規格：JIS、ASA、DIN 或 BS 可供選擇
- 精確度：± 2% 讀取值。
- SMALLEST READABLE QUANTITY：0.01 m


### Remarks :

- Service：Clear Water, Waste Water (strainer required)
- Flanged ends：with drilling to JIS, ASA, DIN or BS.
- ACCURACY：± 2% of the flow range
- SMALLEST READABLE QUANTITY：0.01 m

### SPECIAL FEATURES

水錶如需保養修理時，不需將整個水錶拆卸，僅將上部機件拆卸送修，並以一鐵蓋蓋住錶體，即可繼續通水。

When the meter needs to fix up, it is not necessary to disassemble all the meter from the pipe, it is only need to take off the upper part of the meter.



新政儀器有限公司

TEL:(02)26940177 (02)26949824 FAX:(02)26946663

www.hsinjeng.com.tw E-mail: hsin.jeng@msa.hinet.net